

4-WHEEL SCOOTER

GOPHER
-NEXT GENERATION-

NEXT GENERATION
PERFORMANCE AND
STYLE

The **Gopher Next Generation** is feature-rich, boasting independent front suspension and mono shock rear suspension, luxurious leg room, 11" tyres and a 160 kg (350 lbs.) weight capacity. Sleek and sporty, the Gopher Next Generation is exceptional in its class.



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®


www.pridemobility.com.au

SPECIFICATIONS

GOPHER- NG[®] 4-wheel

Weight capacity:	160kg (350 lbs.)
Maximum speed:	Programmable to maximum 8 km/h (4.9 mph)
Ground clearance ² :	6cm (2.36")
Turning radius:	139.5cm (55")
Overall length ²	137cm (54")
Overall width ²	67cm (26.4")
Tyres:	Pneumatic Front: 27.94cm (11") Rear: 27.94cm (11")
Suspension:	Independent front, mono shock rear
Per-charge range ^{1,4} :	Up to 25 km (15.5 miles)
Total w/o batteries:	75.2 kg (165.44 lbs.)
Braking System:	Electronic, regenerative and electromechanical
Standard Seating:	Foldable moulded plastic Weight: 22 kg (48.5 lbs.) Dimensions: 45.72 cm (18") width x 40.64 cm (16") depth
Drive System:	Rear-wheel drive, sealed transaxle, 24 volt DC motor
Maximum Incline:	8°
Battery requirements ³ :	Type: (2) 12-volt deep cycle Standard Size: 40 Ah Optional: 50 Ah
Battery charger:	5-amp off-board charger

Colours:



Red



Blue

FEATURES

- Independent front suspension, mono shock rear suspension
- Luxurious leg room
- High visibility, front and rear lighting package
- Easy-drive tiller with wraparound handles
- Sleek, modern styling
- 11" pneumatic front and rear tyres
- Programmable to maximum 8 km/h (4.9 mph)
- 160 kg (350 lbs.) weight capacity



High visibility rear lighting

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can

be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards.

Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

Pride
Mobility Products
Australia Pty. Ltd.

PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]



(Tel) 03 8770 9600 • (Fax) 03 9703 2720

20-24 Apollo Drive Hallam, Victoria 3803

ACN 088 609 661 ABN 66 088 609 661

www.pridemobility.com.au

