

Economy Class Scooter with **Great Outdoor Stability** and Impressive Features.



4-Wheel Scooter



The **Pathrider® ES 10** delivers great outdoor stability, ease of use and maximum value. Features include a bright headlight, adjustable tiller and stylish design.

PRIDE® **MOBILITY** SCOOTERS
LIVE YOUR BEST®

| pridemobility.com.au |





Specifications 4W: S104

Weight Capacity	158 kg (350 lbs.)
Maximum Speed ¹	Up to 8.8 km/h (5.5 mph)
Ground Clearance ²	8.89 cm (3.5") (at mid-frame)
Turning Radius ²	132.08 cm (52") (left)
Overall Length ²	119.4 cm (47")
Overall Width ²	57.15 cm (22.5")
Front Tyres	25.4 cm (10") solid
Rear Tyres	25.4 cm (10") solid
Range Per Charge ^{2,4}	17.92 km (11 miles) (with U-1 batteries)
Total Weight Without Batteries	52.3 kg (115.5 lbs.)
Heaviest Piece When Disassembled	25.8 kg (57 lbs.) front section
Standard Seating	<i>Type:</i> Foldable, compact, vinyl-covered, molded plastic <i>Weight:</i> 9.75 kg (21.5 lbs.) <i>Material:</i> Black Vinyl <i>Dimensions:</i> Width: 45.7 cm (18") Depth: 43.2 cm (17")
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Electronic, regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12V deep-cycle Size: U-1 (30-34 AH) Weight: 11 kg (24.5 lbs.) each
Battery Charger	Off-board, 3 amp
Color	Red



Features

- Disassembles for transport or storage
- Backlit battery gauge
- Bright LED headlight
- Seat features viscoelastic foam inserts for increased comfort and slider for enhanced positioning
- Adjustable tiller
- 158 kg (350 lbs.) weight capacity



EASY-TO-USE TILLER

Optional Accessories

- Pride® rear bag (includes crutch/walking stick holder)
- Walker holder (must have Pride® rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.



20-24 Apollo Drive Hallam, Victoria 3803
ACN 088 609 661 ABN 66 088 609 661



(Tel) 03 8770 9600 • (Fax) 03 9703 2720 • www.pridemobility.com.au

