PRIDE MOBILITY

<16.9 km
Range per Charge

136 kg
Weight Capacity

116.2 cm
Turning Radius

GO GO® LX WITH CTS SUSPENSION

The Smoothest Ride in Travel Mobility

The Go Go® LX with CTS suspension blends sleek design with powerful performance, ensuring a smooth ride with its industry-leading suspension system. It's portable and effortlessly disassembles, ideal for those on the go. Featuring feather-touch disassembly, a wraparound delta tiller (with charger port), non-scuffing tyres, LED headlight, and front basket, it's perfect for riders who plan to take the road less travelled every once in a while.

Visit **pridemobility.com.au** for more information

GO-GO LX WITH CTS SUSPENSION

All Around CTS Suspension

Feather Touch Disassembly

Removable Battery Box

RANGE PER CHARGE (MAX)[1]	Up to 16.9 km
MAXIMUM WEIGHT CAPACITY	136 kg
TURNING RADIUS	116.2 cm
MAXIMUM SPEED[1]	7 km/h
LENGTH & WIDTH[2]	L: 104 cm W: 52.1 cm
SEAT TYPE WIDTH & DEPTH (STANDARD)	Compact, foldable seat W: 43 cm (17") D: 43 cm (17")
SEAT-TO-DECK HEIGHT	41.3 cm - 43.8 cm
SEAT-TO-GROUND HEIGHT	52.7 cm - 56.5 cm
GROUND CLEARANCE[5]	6.4 cm at frame 3.8 cm at motor

OVERALL WEIGHT (NOT INC BATTERY)[2]	39.4 kg
WEIGHT OF HEAVIEST PIECE	16.6 kg (front section)
SUSPENSION	front & rear CTS
3W/4W OPTION	4W
FRONT TYRES	7" solid
REAR TYRES	8" solid
BATTERY REQUIREMENTS[4]	(2) 18Ah
BATTERY CHARGER	Off-board, 2A
BATTERY WEIGHT	6 kg each
COLOUR OPTIONS[6]	Red Blue

1. Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
2. Includes standard seat weight.
3. Width of base (not including seat).
4. Deep cycle (AGM or gel cell type recommended)
5. Does not account for anti-tip clearance.
6. All shroud panels included

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.

PRIDE MOBILITY

20-24 Apollo Drive, Hallam, Victoria 3803 I (03) 8770 9600 I www.pridemobility.com.au

Certified System
Quality
ISO 9001
SAI GLOBAL